



SPRAYS
RIGHTSIDE UP
UPSIDE DOWN

Mr. Mechanic
Lubricant

Mr. Mechanic

Lubricant Lubricante

Four Way Protection
Cleans, Lubricates, Penetrates
Prevents Rust

DANGER / PELIGRO:

FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL

INFLAMABLE
DAÑINO O FATAL SI ES INGERIDO
CONTENIDO BAJO PRESIÓN
NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONALES EN LA PARTE TRASERA

NET WT. 12 OZ. (340 g)

QUEST CHEMICAL CORPORATION
HOUSTON, TEXAS 77041

Will loosen dirt and scale from painted and plated surfaces. Remove loosened scale and spray again to cover surface.

TO LOOSEN BOUND PARTS: Liberal application will loosen threads, tighten fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion.

This product forms a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture. It seals all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Also lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard. Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected by the formula. Can be used on either dry or wet surfaces. To insure adequate protection, periodic checks should be made to determine the need for reapplication.

DIRECTIONS FOR USE: Spray liberally directly on areas to be treated. Reapply periodically as required.

MODO DE EMPLEO: Rocíe libremente el área que será tratada. Repita periódicamente según se requiera.

DANGER: FLAMMABLE. Contains Petroleum Distillates. Do not use near fire or open flame. Contents under pressure. Do not puncture. Do not store above 120°F. Do not throw container into fire or incinerator. Avoid frequent or prolonged contact with skin. Use only in

well ventilated area. If swallowed, do not induce vomiting. Contact physician immediately.

PELIGRO: INFLAMABLE. Contiene destilados de petróleo. No se use cerca del fuego o llama abierta. Contenido bajo presión. No se agujere. No se almacene a temperaturas por encima de 120°F. No tire el contenedor al fuego o incinerador. Evite el contacto frecuente o prolongado con la piel. Usese solo en áreas bien ventiladas. Si es ingerido, no induzca vomito. Contacte al médico inmediatamente.

INGREDIENTS (CAS#): Petroleum Distillate (64741-44-2), Isoparaffinic Hydrocarbon (64742-47-8), Propane/n-Butane (68476-86-8), Petroleum Distillate (64742-54-7), Ethyl Acetate (141-78-6).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A



ITEM 534

Made in USA