



Technical Data Report

DYNAMITE BUTYL CLEANER

DESCRIPTION

DYNAMITE is a USDA authorized heavy duty cleaner. Can be diluted up to 40:1 with water. Use for general purpose cleaning. Removes dirt, grease, oil, and most other soils quickly and easily. Can be used in steam cleaners, warm or cold water, and rotary machines. Also used for cleaning carpets, walls, and industrial machinery. Contains solvents, detergents, emulsifiers, wetting agents, sequestering agents, penetrants, and corrosion inhibitors.

APPLICATIONS

Use to clean grease, grime, oil, soot, food, dirt, mud, ink, carbon, and lipstick. Areas of use include restaurants, hotels/motels, apartments, industrial plants, offices, schools, drilling rigs and stores.

FEATURES & BENEFITS

- Powerful formula removes even the toughest soils.
- Safe to use on painted surfaces, metals and other inanimate objects. Contains no caustics, acids or abrasives.
- Rinses completely and quickly from all surfaces.

SPECIFICATIONS

FORM: Liquid
ODOR: Mild Sweet
COLOR: Red
DETERGENCY: Strong
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 year +
COLD STABILITY: 32° F
PHOSPHATES: <3%

FLASH POINT: None
BOILING POINT: 212° F +
SOLUBILITY IN WATER: 100 %
SPECIFIC GRAVITY: 1.09
% VOLATILE BY VOLUME: 90%
pH: 13.7
VISCOSITY: Thin
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

DYNAMITE BUTYL CLEANER

This product is a concentrated industrial cleaner. For use on walls, carpet, floors, vinyl upholstery, metal surfaces, machinery, counter tops. Removes grease, oil, tar, wax, carbon, soot, smoke, ink, lipstick, food stains and heavy grime.

DIRECTIONS FOR USE

GENERAL PURPOSE CLEANING: Dilute up to 40:1. Use as outlined below for specific cleaning jobs.

WALLS: Mix 1-12 and spray, holding sponge underneath to prevent solution from running down and leaving clean streaks. On large areas clean from bottom up.

SHAMPOO: Mix 1-12 with warm water and use in dry foam or rotary shampoo machine. Do not over wet carpet.

WAX REMOVAL: Mix 1-16 with hot water. Apply to floor generously. Wait 10 minutes, then scrub with nylon pad.

VINYL UPHOLSTERY: Mix 1-8 with warm water. Spray. Wait 30 seconds. Wipe with sponge.


DEGREASING: Mix 1-9 and apply to motors or machinery. Allow to penetrate 3-4 minutes. Wash with hose or power sprayer.

DISCOLORED PAINT ON CARS AND TRUCKS: Mix 1-16 with warm water. Spray on. Wait 10 seconds. Wipe clean.

WARNING: Harmful if swallowed. Vapor harmful. May cause irritation to skin and eyes. Avoid excessive inhalation or contact with skin. Use in a well ventilated area. If swallowed, give 1 or 2 glasses of water and contact physician. If in eyes, flush thoroughly with water and contact physician. Wash skin with soap and water when using.

Contains (CAS #):Water (7732-18-5), 2-Butoxy Ethanol (111-76-2), Sodium metasilicate pentahydrate(6834-92-0), Phosphate ester (N/A), Sodium hydroxide (1310-73-2)

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

Available in gallons (4/cs), 55 gallon drum, 35 gallon drum, 20 gallon drum, 5 or 6 gallon pail.