

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 534
IDENTITY: MR. MECHANIC
Revision Date: 10/20/2010
-----

Section I
-----

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188
-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include ETHYL ACETATE, HEAVY PARAFFINIC PETROLEUM, ISOPARAFFINIC HYDROCARBON, LT PARAFFINIC PET. OIL, MINERAL SEAL OIL, PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 180 Specific Gravity (water=1) 0.83
Vapor Pressure(mm Hg) >3 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: THIN BROWN LIQUID WITH STRONG SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):+110F TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: DRY CHEMICAL, FOAM, AND CO2.
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPRATUS.
May develop a flammable atmosphere in confined areas, vapors are heavier
than air and can travel to source of ignition.
Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

