



# MR. MECHANIC

## LUBRICANT

### DESCRIPTION

MR. MECHANIC is a USDA authorized greaseless light duty lubricant for general use. Contains a light mineral oil in a petroleum distillate base with a corrosion preventative for long lasting protection. Lubricates, penetrates and prevents rust giving four-way protection.

### APPLICATIONS

Lubricates and prevents corrosion of nuts, bolts, corroded parts, door hinges, locks, machine parts, gears, slides, wire cable, and other turning and sliding parts. For use around garages, oil rigs, homes, machine shops, assembly plants, electronics repair shops, service stations, locksmiths, industrial shops, factories, and air conditioner repair shops.

### FEATURES & BENEFITS

- Aerosol packaging allows convenient use on small parts and for spot applications, Eliminates waste due to drips and spills.
- Convenience of a four-in-one product. Lubricates, penetrates, displaces moisture, prevents corrosion.

Note: Spray is flammable. Do not apply in the presence of possible sources of ignition of residual liquid or vapors (such as active electrical circuits, switches, running motors or flames).

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol  
**ODOR:** Sweet  
**COLOR:** Amber  
**DETERGENCY:** None  
**TOXICITY:** 400 ppm OSHA TLV  
**WETTING ABILITY:** Saturates  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** 110°F TCC  
**FLAME EXTENSION:** 18"  
**SOLUBILITY IN WATER:** 0%  
**SPECIFIC GRAVITY:** 0.83  
**% VOLATILE BY VOLUME:** 20%  
**pH:** N/A  
**PROPELLANT:** Hydrocarbon  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** None

### LABEL INFORMATION

#### MR. MECHANIC LUBRICANT SPRAY

Will loosen dirt and scale from painted and plated surfaces. Remove loosened scale and spray again to cover surface.

**TO LOOSEN BOUND PARTS:** Liberal application will loosen threads, tighten fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion.

This product forms a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture. It seals all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Also lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard.


Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected by the formula. Can be used on either dry or wet surfaces. To insure adequate protection, periodic checks should be made to determine the need for reapplication.

**DIRECTIONS FOR USE:** Spray liberally directly on areas to be treated. Reapply periodically as required.

**DANGER: FLAMMABLE.** Contains Petroleum Distillates. Do not use near fire or open flame. Contents under pressure. Do not puncture. Do not store above 120° F. Do not throw container into fire or incinerator. Avoid frequent or prolonged contact with skin. Use only in well ventilated area. If swallowed, do not induce vomiting. Contact physician immediately.

**CONTAINS (CAS#):** Petroleum Distillate (64741-44-2), Isoparaffinic Hydrocarbon (64742-47-8), Propane/n-Butane (68476-86-8), Heavy Paraffinic Petroleum (64741-88-4), Light Paraffinic Petroleum Oil (64741-89-5), Ethyl Acetate (141-78-6).

|              |   |
|--------------|---|
| HEALTH       | 1 |
| FLAMMABILITY | 3 |
| REACTIVITY   | 1 |
| PERSONAL     | A |



### PACKAGING INFORMATION

12 - 16 oz cans per case, 12 oz net weight