

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 550
IDENTITY: PIERCE
Revision Date: 03/22/2010

Section I

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 0 HEALTH: 2 PERSONAL PROTECT: G

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include CARBON DIOXIDE, MINERAL SEAL OIL, and TETRACHLOROETHYLENE.

Comment:
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN
TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 250 F Specific Gravity (water=1) 1.44
Vapor Pressure(mm Hg) 11 Melting Point: N/A
Vapor Density(AIR=1) 5.7 Evaporation Rate: >2
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, TYPICAL CHLORINATED SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards: UNDER PRESSURE & EXPOSURE TO TEMPERATURS
ABOVE 120 F MAY CAUSE BURSTING. CONTAINER MAY VENT OR RUPTURE DUE TO FIRE.
VIOLENT STEAM GENERATION MAY OCCUR UPON APPLICATION OF DIRECT WATER STREAM.

