



PIERCE PENETRATING LUBRICANT

DESCRIPTION

PIERCE Penetrating Lubricant is a USDA authorized lubricating product. Formulated to quickly penetrate rust, corrosion and moisture. Lubricates, cleans and contains rust preventative. Non-flammable and non-conductive to 30,000 volts. Four way action cleans, lubricates, prevents rust and penetrates.

APPLICATIONS

For use on motors, wire cable, rusted parts, ignition systems, machine parts, door hinges, locks, nuts & bolts, and refrigeration equipment. Areas of use include homes, hotel/motels, airplanes, cars & trucks, machine shops, oil rigs, manufacturing facilities, industrial plants, and factories.

FEATURES & BENEFITS

- Versatile light duty formula penetrates, lubricates, prevents corrosion and displaces moisture.
- Silicone free formula will not interfere with subsequent painting.
- Nonflammable.
- Meets MIL Spec C-2344

SPECIFICATIONS

FORM: Solvent base aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 50 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0° F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.44
% VOLATILE BY VOLUME: 87%
pH: None
PROPELLENT: CO₂
EVAPORATION RATE: Moderate
BIODEGRADABILITY: No

LABEL INFORMATION

PIERCE PENETRATING LUBRICANT

Is a non-flammable powerful, multiple-action penetrant and protective shield. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.

SUGGESTED USES

- Start Wet Engines
- Electrical Panel Board
- Remove Moisture from Ignition Wires
- Airplanes
- Laundromats
- Freeing Nuts & Bolts
- Parking Meters
- Stops Corrosion on Battery Terminals
- Vending Machines
- Refrigeration Equipment

DIRECTIONS

Spray liberally directly on area to be treated. Reapply periodically as required.

HEALTH	2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	A


CAUTION

Vapor Harmful. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F.

Contains chlorinated solvents. If sprayed in eyes, flush with large amounts of water. Avoid excessive inhalation. Avoid prolonged or repeated contact with skin.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Petroleum Distillate (64741-44-2), Carbon Dioxide (124-38-9), Sorbitan Monooleate (1338-43-8), Methyl Salicylate (119-36-8)



PACKAGING INFORMATION

12 - 16 oz cans per case 16 oz net weight