



GREENSCAPES

PENETRATING OIL

DESCRIPTION

GREENSCAPES PENETRATING OIL is designed with biodegradable ingredients to safely and responsibly penetrate rust and corrosion and displace moisture. Quickly loosens frozen and rusted parts. Leaves a long lasting lubricating residual to provide reduced friction, less wear and quiet, efficient operation. Oil film provides a chemical barrier to repel moisture. Dries wet ignitions. Will not interfere with circuits or electrical equipment up to 22,000 volts.

APPLICATIONS

Ideal for tools, autos, aircraft, boats, ships, winches, swivels and more. For use in manufacturing plants, maintenance, marinas, truck and auto fleets, refineries, schools, pipelines and offshore. .

FEATURES & BENEFITS

- Cap utilizes 72% less plastic than standard aerosol caps
- No VOCs are emitted during manufacturing of can
- Can made of recyclable steel
- Can does not require detinning prior to recycling
- Formulated with biodegradable ingredients
- No harsh fumes or chemicals

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Citrus
COLOR: Light Yellow
DETERGENCY: N/A
TOXICITY: 1000 ppm OSHA PEL
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: >500°F
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.91
% VOLATILE BY VOLUME: 9.5%
pH: N/A
PROPELLENT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

GREENSCAPES PENTETRATING OIL

Designed with biodegradable ingredients to safely and responsibly penetrate rust and corrosion and displace moisture. Quickly loosens frozen and rusted parts. Leaves a long-lasting lubricating residual to provide reduced friction, less wear and quiet, efficient operation. Oil film provides a chemical barrier to repel moisture. Dries wet ignitions. Will not interfere with circuits or electrical equipment up to 22,000 volts.

DIRECTIONS FOR USE: Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Apply periodically as required.

CAUTION: Contents under pressure. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Never throw container into fire or incinerator.

CONTAINS (CAS #): Soybean Oil (8001-22-7), Propane/n-Butane (68476-86-8)

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 20 oz cans per case, 14 oz net weight