

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 562
IDENTITY: GREENSCAPES PEN W/ TEFLON Revision Date: 01/25/2010

Section I

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 0 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include 1,8-P-MENTHADIENE, PROPANE, and SOYBEAN OIL.

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: >350 F Specific Gravity (water=1) 0.91
Vapor Pressure(mm Hg) N/A Melting Point: N/A
Vapor Density(AIR=1) N/A Evaporation Rate: >1
Solubility in Water: NONE (Butyl Acetate=1)
Appearance and Odor: CITRUS ODOR, YELLOW LIQUID

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):>500F COC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: DRY CHEMICAL FOAM OR CO2
Special Fire Fighting Procedures: CLASS B FIRE; APPLICATION OF WATER TO
BURNING OIL CAN CAUSE SPLATTERING, OIL WILL FLOAT ON WATER.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 562

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING
Incompatibility (Materials to Avoid): STRONG OXIDIZING AGENTS.

Hazardous Decomposition or Byproducts: OXIDES OF CARBON.

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
SKIN: REPEATED CONTACT WITH SKIN MAY CAUSE DEFATTING OF TISSUE
INGESTION AND INHALATION: NO TOXICITY EXPECTED. EYE: MAY CAUSE IRRITATION.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO
Signs and Symptoms of Exposure: SEE ABOVE HEALTH HAZARDS.

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: SKIN: WASH WITH SOAP AND WATER.
EYES: RINSE WITH WATER FOR 15 MINUTES.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.
NO SPECIFIC HAZARDS: MATERIAL IS NON-HAZARD.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing:
EXPOSURES TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: NONE KNOWN

Section VIII: CONTROL MEASURES

Respiratory Protection: NONE REQUIRED
Ventilation: Local Exhaust: N/A
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE ALWAYS RECOMMENDED WHEN USING CHEMICALS.
Other Protective Clothing or Equipment:
NONE REQUIRED
Work/Hygienic Practices:
WASH HANDS AFTER USE.