



# GREENSCAPES

## PENETRATING OIL WITH PTFE

### DESCRIPTION

GREENSCAPES PENETRATING OIL WITH PTFE is designed with biodegradable ingredients to safely and responsibly penetrate rust and corrosion and displace moisture. Contains PTFE to continuously provide lubrication after application. Reduces friction, wear and tear and noise. Contains a corrosion inhibitor to protect metal parts.

### APPLICATIONS

Ideal for wire cable, door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, blocks and tackle, conveyors, construction machinery, industrial parts and locks. Applications include farming, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, manufacturing plants, textile mills, lumber mills, cement plants and automotive/motorcycle/marine repair.

### FEATURES & BENEFITS

- Cap utilizes 72% less plastic than standard aerosol caps
- No VOCs are emitted during manufacturing of can
- Can made of recyclable steel
- Can does not require detinning prior to recycling
- Formulated with biodegradable ingredients
- No harsh fumes or chemicals

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol  
**ODOR:** Citrus  
**COLOR:** Light Yellow  
**DETERGENCY:** N/A  
**TOXICITY:** 1000 ppm OSHA PEL  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 32°F  
**PHOSPHATES:** None

**FLASH POINT:** >500°F  
**FLAME EXTENSION:** None  
**SOLUBILITY IN WATER:** None  
**SPECIFIC GRAVITY:** 0.91  
**% VOLATILE BY VOLUME:** 9.59%  
**pH:** N/A  
**PROPELLENT:** Hydrocarbon  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** Yes

### LABEL INFORMATION

#### GREENSCAPES PENTETRATING OIL WITH PTFE

Designed with biodegradable ingredients to safely and responsibly penetrate rust and corrosion and displace moisture. Contains PTFE to continuously provide lubrication after application. Reduces friction, wear and tear and noise. Contains a corrosion inhibitor to protect metal parts.

**DIRECTIONS FOR USE:** Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Apply periodically as required.

**CAUTION:** Contents under pressure. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Never throw container into fire or incinerator.

**CONTAINS (CAS #):** Soybean Oil (8001-22-7), Propane/n-Butane (68476-86-8).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



### PACKAGING INFORMATION

12 – 20 oz cans per case, 14 oz net weight