



GREENSCAPES

METAL PROTECTOR

DESCRIPTION

GREENSCAPES METAL PROTECTOR is designed to safely and responsibly coat metal parts and surfaces for indefinite indoor protection and long-lasting outdoor protection. Provides a flexible, non-tacky, dust-resistant coating which will not crack, peel, fade or check over a long period of time. Coating is transparent amber to allow data on the part or tool to be easily identified. Sets up in approximately 2 hours. To remove, use kerosene or mineral spirits. Weldable and paintable. Highly resistant to salt spray and other harsh elements.

APPLICATIONS

Ideal for metal parts, dies, castings, pulleys, hoists, tools, pipe thread, cables, riggings.

FEATURES & BENEFITS

- Cap utilizes 72% less plastic than standard aerosol caps
- No VOCs are emitted during manufacturing of can
- Can made of recyclable steel
- Resistant to salt spray and harsh elements.
- Can does not require detinning prior to recycling
- Formulated with biodegradable ingredients
- No harsh fumes or chemicals

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Citrus
COLOR: Light Yellow
DETERGENCY: N/A
TOXICITY: 1000 ppm OSHA PEL
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: >500°F
FLAME EXTENSION: None
SOLUBILITY IN WATER: None
SPECIFIC GRAVITY: 0.9
% VOLATILE BY VOLUME: 9.5%
pH: N/A
PROPELLENT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

GREENSCAPES METAL PROTECTOR

Designed to safely and responsibly coat metal parts and surfaces for indefinite indoor protection and long-lasting outdoor protection. Provides a flexible, non-tacky, dust-resistant coating which will not crack, peel, fade or check over a long period of time. Coating is transparent amber to allow data on the part or tool to be easily identified. Sets up in approximately 2 hours. To remove, use kerosene or mineral spirits. Weldable and paintable. Highly resistant to salt spray and other harsh elements.

DIRECTIONS FOR USE: Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Apply periodically as required.

CAUTION: Contents under pressure. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Never throw container into fire or incinerator.

CONTAINS (CAS #): Soybean Oil (8001-22-7), Propane/n-Butane (68476-86-8).

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 1 |
| REACTIVITY | 0 |
| PERSONAL | A |



PACKAGING INFORMATION

12 – 20 oz cans per case, 14 oz net weight