



RUST RELEASE LUBRICANT

FOAMING PENETRATING & CUTTING OIL

DESCRIPTION

RUST RELEASE provides effective lubrication in a variety of metalworking applications. The anti-friction properties prolong tool life. For use on farm equipment, sports equipment, industrial equipment, marine & auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.

APPLICATIONS

Formulated to loosen rusted parts and lubrication as well as cutting or machining carbon alloys, stainless steel, chrome steel, copper, aluminum, magnesium, and bronze. Lubricates door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, block & tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Reduces metal-to-metal noise.
- Resists rust and corrosion even in extreme conditions.
- Prolongs tool life.

SPECIFICATIONS

FORM: Oil Base Aerosol
ODOR: Petroleum Oil
COLOR: Straw Colored
DETERGENCY: None
TOXICITY: 100 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 year plus
COLD STABILITY: 0° F
PHOSPHATES: None

FLASH POINT: 200° F plus
FLAME EXTENSION: 18" plus
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.92
% VOLATILE BY VOLUME: 26
pH: N/A
PROPELLENT: Hydrocarbon
EVAPORATION RATE: Very Slow
BIODEGRADABILITY: No

LABEL INFORMATION

RUST RELEASE
FOAMING PENETRATING & CUTTING OIL

This product is designed to be used on farm equipment, sports equipment, industrial equipment, marine & auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.


DIRECTIONS

Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

WARNING: FLAMMABLE. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F. Keep out of reach of children. Contains petroleum distillates. If swallowed, contact physician immediately. Do not induce vomiting.

CONTAINS (CAS #): Light Naphthenic Petroleum Distillate (64742-53-6), Propane/n-Butane (68476-85-7), Heavy Naphthenic Petroleum Distillate (64742-52-5), Oxygenated Hydrocarbon (N/A), Mineral Spirits (8052-41-3)

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

12 - 20 oz cans per case 16 oz net weight