



QUIK-ZINC GALVANIZE COATING

FOAMING PENETRATING & CUTTING OIL

DESCRIPTION

QUIK-ZINC is a high quality, high solids, heavy duty zinc coating designed to give superior corrosion protection. Protects ferrous metal from oxidation by bonding with it electrochemically. Prevents rust by galvanic action, dries to a flexible coating that bends without chipping. Can be used as a protective final coating or primer wherever iron or steel will be exposed to atmospheric or corrosive conditions.

APPLICATIONS

Areas of use include bus barns, refineries, pipe yards, oil rigs and industrial plants. For iron & steel surfaces, air conditioners, truck & auto fleets, automotive bodies, agriculture equipment, fences, metal roofs, metal buildings, metal fabricators, railroad equipment and marine equipment.

FEATURES & BENEFITS

- Will not crack, peel, or yellow even under extreme conditions.
- 93% pure zinc after drying.
- Provides excellent adhesion to all metal surfaces.
- Dries to a flexible, paintable coating.

SPECIFICATIONS

FORM: Solvent Base Aerosol	FLASH POINT: 60-70° F
ODOR: Solvent	FLAME EXTENSION: 18"
COLOR: Grey	SOLUBILITY IN WATER: None
DETERGENCY: None	SPECIFIC GRAVITY: 1.00
TOXICITY: 100 ppm OSHA TLV	% VOLATILE BY VOLUME: 66%
WETTING ABILITY: N/A	pH: N/A
STORAGE STABILITY: 1 Year	PROPELLENT: Hydrocarbon
COLD STABILITY: 32° F	EVAPORATION RATE: Moderate
PHOSPHATES: N/A	BIODEGRADABILITY: No
TEMPERATURE TOLERANCE: Continuous 250°F Intermittent 300°F	

LABEL INFORMATION

QUIK-ZINC GALVANIZE COATING

This product is designed to protect iron and steel surfaces from rust and corrosion. Its high zinc content assures maximum protection on metal surfaces. Dries quickly to a hard film containing 93% zinc dust. Provides two way protection, first with the high zinc content protective coating, secondly with true galvanic action. Galvanic action is effective when surface is scratched, broken or dissipated and moisture is present. Easy to apply. Compares to a hot dip galvanize when applied as a 3 mil thickness. Formulated for use in presence of moisture, salts and acids.


DIRECTIONS

Shake can for a full sixty (60) seconds after rattling of mixing ball begins. If application is to cover a large area, periodically shake can to insure uniform mixing of the contents. Surface to be sprayed should be clean and dry. Remove protective cap and point opening in spray nozzle towards surface to be sprayed. Holding can 10 to 12 inches from the surface, apply in thin, even coats until surface is completely covered. Allow 5 to 10 minutes after application before handling. After spraying, turn can upside down and spray until no more zinc is evident. This product is best applied at room temperature (70-80° F.)

DANGER: Contents Under Pressure. Extremely Flammable. Keep out of reach of children. Exposure to temperatures above 120° F may cause bursting. Keep away from heat, sparks or open flame. Use only in a well ventilated area. Do not puncture or incinerate container. Vapor harmful. Contains acetone and xylene. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call physician immediately.

CONTAINS (CAS #): Xylene (1330-20-7), Zinc (7440-66-6), Propane/n-Butane (68476-86-8), Acetone (67-64-1), Organophilic Clay (N/A)

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

12 - 16 oz cans per case 14 oz net weight