



TRAILERBRITE

ALUMINUM BRIGHTENER

**DANGER: POISON**

DESCRIPTION

TRAILERBRITE is a hydrofluoric acid based aluminum cleaner and brightener. Highly concentrated. Powerful. Contains a blend of acids, detergents and corrosion inhibitors that prevent acids from attacking metal surfaces. Removes oxidation, corrosion and scale. Leaves surface bright and shiny.

APPLICATIONS

For use by industrial plants, chemical plants, freight and trucking companies and buildings. Formulated specifically for aluminum trailers and tanks. Can also be used on steel surfaces and aluminum frames.

FEATURES & BENEFITS

- Oxidizes corrosion and scale
- Brightens surface
- Highly concentrated and powerful

SPECIFICATIONS

FORM: Liquid
ODOR: Pungent
COLOR: Blue
DETERGENCY: Excellent
TOXICITY: 1MG / M²
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: Excellent
PHOSPHATES: None

FLASH POINT: None
BOILING POINT: 212°F +
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 1.08
% VOLATILE BY VOLUME: 83%
pH: 1.0
VISCOSITY: Thin
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

TRAILERBRITE ALUMINUM BRIGHTENER

SPECIFICALLY FOR ALUMINUM AND STAINLESS STEEL TRAILERS. DO NOT USE ON OTHER SURFACES SUCH AS ALUMINUM WHEELS OR ALUMINUM ENGINE BLOCKS. IF SPLASHED ON GLASS, WASH OFF IMMEDIATELY. ALWAYS DILUTE WITH WATER BEFORE USING. Mix solution in a plastic or stainless steel bucket or sprayer. Make up only enough solution for the job at hand.

FOR CLEANING TRUCKS AND TRAILERS – Under average conditions of temperature (55-85°F) and relative humidity (50%), a solution of 1 part concentrate diluted with 20 parts water will give good results. Since lower temperatures slow cleaning action use a stronger solution on cool days.

NOTE: Working in hot direct sun may cause streaking – wet down sides of trailer to cool surface before applying. Whenever possible, it is better to work in the shade.


TO APPLY: Spray product and agitate with a soft brush. Always work from the bottom up to avoid streaking and also work only small areas so surface does not dry out before rinsing. After Solution has set for about 5 minutes, flush thoroughly with water, being sure to also rinse adjacent concrete ramps, floors and drains.

DANGER: POISON. Hazardous liquid and vapor. Contains Hydrofluoric Acid. Causes burns which may not be immediately painful or visible.

PRECAUTIONS: Do not get in eyes, on skin, or on clothing. Do not breathe vapor. Store out of sun and away from direct heat. WEAR RUBBER APRON, PLASTIC FACE SHIELD OR GOGGLES AND CAP FOR PROTECTION. WEAR RUBBER GLOVES. BEWARE THAT WIND DOES NOT BLOW ALUMINUM BRIGHTENER BACK ON YOU! FIRST AID: If splashed on skin or eyes, flush at once with plenty of water. Contact a physician immediately. If medical attention is delayed apply a mixture of glycerin with milk of magnesia to skin. Remove and wash clothing before re-use. D.O.T. description: Liquid cleaning compound (containing hydrofluoric acid). FOR INDUSTRIAL USE ONLY! NOT FOR HOUSEHOLD USE. KEEP OUT OF REACH OF CHILDREN.

CONTAINS (CAS#): Water (7732-18-5), Hydrogen Flouride (7664-39-3), Sulfuric Acid (7664-93-9), 2-Butoxy Ethanol (111-76-2) Acid Foamer (N/A).

HEALTH	3
FLAMMABILITY	0
REACTIVITY	2
PERSONAL	D



PACKAGING INFORMATION

Available in 4x1 gallons, 5 and 6 gallon pails, and 20, 35 and 55 gallon drums.