



Product # 825

## Technical Data Report

# CRUNCH

## ENGINE DEGREASER



### DESCRIPTION

Crunch is a USDA authorized concentrated blend of organic solvents in a gel base. The gel base allows product to cling to vertical surfaces. It works quickly to penetrate and emulsify tar, asphalt, grease and oil. It washes off with water or solvent. This product is safe and easy to use. Spray on and wash off with water. Does not contain 1,1,1 Trichloroethane, CFCs or petroleum distillates.

### APPLICATIONS

For use on tar, grease, oil, asphalt based roofing compounds, and asphalt based cements. Areas of use include automobile dealers, machine shops, industrial manufacturing, factories, fleet maintenance shops, and marine equipment.

### FEATURES & BENEFITS

- Gel-Base – Will Not Run – Spray On – Wash Off
- Contains No Chlorinated or Fluorinated Solvents
- Natural Citrus Solvent Base. No Offensive Odor.

### SPECIFICATIONS

**FORM:** Solvent Base Aerosol  
**ODOR:** Mild Citrus  
**COLOR:** Clear  
**DETERGENCY:** Excellent  
**TOXICITY:** 400 ppm OSHA TLV  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 year +  
**COLD STABILITY:** 0° F  
**PHOSPHATES:** None

**FLASH POINT:** >150° F TCC  
**FLAME EXTENSION:** <18”  
**SOLUBILITY IN WATER:** 100%  
**SPECIFIC GRAVITY:** 0.95  
**% VOLATILE BY VOLUME:** 70%  
**pH:** 12.4  
**PROPELLENT:** Hydrocarbon  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** Yes

### LABEL INFORMATION

CRUNCH  
 ORGANIC ENGINE DEGREASER

A USDA authorized concentrated blend of organic solvents in a gel base. The gel base allows product to cling to vertical surfaces. It works quickly to penetrate and emulsify tar, asphalt, grease and oil. It washes off with water or solvent. This product is safe and easy to use. Spray on and wash off with water. Authorized for use in meat and poultry processing plants by the USDA. Does not contain chlorinated or fluorinated solvents.

#### DIRECTIONS FOR USE

When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar.

**FOR ENGINES:** Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminium foil and run engine for fifteen minutes to insure complete drying.

**OTHER SURFACES:** To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

**DANGER:** Flammable. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120° F may cause bursting. Avoid prolonged contact with skin and eyes. If swallowed, do not induce vomiting. Call a physician immediately. Use with adequate ventilation.

**CONTAINS (CAS #):** Propane/nButane (68476-86-8), Water (7732-18-5), Citrus Terpene (CAS# 5989-27-5), Isoparaffinic Hydrocarbon (64742-47-8), Nonionic Surfactant (CAS# 25154-52-3).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	1
PERSONAL	A



### PACKAGING INFORMATION

12 - 20 oz cans per case 15 oz net weight