



BIG RED

PREMIUM NON-MELT MULTI-PURPOSE GREASE

DESCRIPTION

BIG RED is a multi-purpose, red, non-melt grease containing graphite for automotive, marine, industrial, and agricultural applications. Extreme pressure additives give excellent resistance to shock and impact. Forms a protective film to guard against rust and corrosion. Provides additional lubrication in applications where metal meets metal. Resists chemical breakdown from acids, salt water, dust and dirt. Will not liquify at high temperatures like soap based greases and remains pumpable at low temperatures.

APPLICATIONS

Excellent for use on high and low speed ball and roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, and fifth wheels. For use in all areas of industrial maintenance.

FEATURES & BENEFITS

- Stays put longer than other greases
- Wide temperature range
- Extreme pressure additives for high loads
- Resists corrosion and resulting seizing of fittings
- Resists acids, salt spray, boiling water, weather, dirt, and oxidation

SPECIFICATIONS

COLOR: Red
THICKENER: Bentone
NLGI GRADE: 3
PENETRATION D-217: 220-250
DROPPING POINT D-566: Non Melt
TEMPERATURE RANGE: 0°F to 600°F
FILLERS: None

TIMKEN OK LOAD: 55 Pounds
BASE OIL: Petroleum Oil
VISCOSITY @ 100°F SUS 800
VISCOSITY @ 210°F SUS 70
FOUR BALL WEAR D-2266: 0.45mm
USDA RATING: H-2

LABEL INFORMATION

BIG RED PREMIUM NON-MELT MULTI-PURPOSE E.P. GREASE

A multi-use grease for hundreds of automotive, marine and agricultural applications. Extreme pressure additives give resistance to shock impact. Does not liquify at high temperatures like soap based greases, yet remains pumpable at low temperatures. Forms a protective film, resists rust and corrosion. Resists chemical break down and oxidation. This waterproof lubricant will not wash out even by boiling water and steam.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with soap and water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

CONTAINS (CAS#): Naphthenic Oil (64742-52-5), Nykon 77 (68953-58-2), Baragel 3000 (N/A), Paratac (0090003-27-4), Heavetex (9003-31-0).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

Available in 14.5 oz tubes (48 per case) and 45- and 120-pound pails.